

ORMER X30

ALL STEEL RADIAL TYRES

ORMER X30	Tyre Info						Rim	Technical Information							Inflated Unloaded Dimension	
	Product Code	Tyre Size	Star Rating	TT/ TL	LI / SI	TRA Code	Rec. Rim (inch)	Speed (km/h)	Inflation Pressure (Bar / psi)	Load Capacity (kg)					Overall Diameter (mm)	Section Width (mm)
										3.5 Bar / 51 Psi	4.0 Bar / 58 Psi	4.5 Bar / 65 Psi	5.0 Bar / 73 Psi	5.75 Bar / 83 Psi		
	*URC025205702OZK	20.5 R25	**	TL	193 A2 / 177 B	L3 / E3	17.00/2.0	10 km / h		8450	9200	9950	10700	11500	1492	520
								50 km / h		6000	6700	7300	-	-		
	*URC025235702OZK	23.5 R25	**	TL	201 A2 / 185 B	L3 / E3	19.50/2.5	10 km / h		10650	11750	12750	13600	14500	1617	597
								50 km / h		7500	8500	9250	-	-		
	*URC025265702OZK	26.5 R25	**	TL	209 A2 / 193 B	L3 / E3	22.00/3.0	10 km / h		13600	15000	16150	17350	18500	1750	673
								50 km / h		9500	10500	11500	-	-		